



DRAGOTACK™ TAPE

A STEGO TECHNOLOGY, LLC INNOVATION | VAPOUR RETARDERS 07 26 00, 03 30 00 | VERSION: 23 JUN 2017

1. PRODUCT NAME

DRAGOTACK TAPE

2. MANUFACTURER

c/o Stego™ Industries, LLC*
 216 Avenida Fabricante, Suite 101
 San Clemente, CA 92672 USA
 Sales, Technical Assistance
 Ph: +1 (877) 464-7834
 international@stegoindustries.com
 www.stegoindustries.com



3. PRODUCT DESCRIPTION

USES: Dragotack Tape is a solvent-resistant, double-sided adhesive strip used to bond and seal Drago™ Wrap Vapour Intrusion Barrier to concrete, masonry, wood, metal, and other surfaces. Dragotack Tape is a flexible and mouldable material to allow for a variety of applications and installations.

COMPOSITION: Dragotack Tape is made from a solvent-resistant blend of synthetic rubber and resins.

SIZE: Dragotack Tape is 51 mm x 15 m (2" x 50'). Dragotack Tape ships 12 rolls in a case.

4. TECHNICAL DATA

TABLE 4.1: PHYSICAL PROPERTIES OF DRAGOTACK TAPE

PROPERTY	TEST	RESULTS
Dimensions		51 mm x 15 m (2" x 50')
Total Thickness		0.76 mm (30 mil)
Colour		Grey
Material		Synthetic rubber blend
Permeance	ASTM F1249	1.7 ng/(m ² *s*Pa) (0.76 mm)
Adhesion to Steel	ASTM D1000	2.19 kN/m width
Chemical Resistance (TCE, PCE, Toluene, Xylene)	ASTM D471 / D543	No significant change to mass or volume.
Installation Temperature		4°C / 43°C
In Service Temperature Range		-29°C / 60°C
VOC Content		No VOCs, 100% solids

Continued...

Note – legal notice on page 2.

DRAGOTACK™ TAPE

A STEGO TECHNOLOGY, LLC INNOVATION | VAPOUR RETARDERS 07 26 00, 03 30 00 | VERSION: 23 JUN 2017

5. INSTALLATION

TO WALLS AND FOOTINGS: Make sure the area of adhesion is free of dust, dirt, debris, moisture, and frost to allow maximum adhesion. Remove release liner on one side and stick to desired surface. When ready to apply Drago Wrap, remove the exposed release liner and press Drago Wrap firmly against DragoTack Tape to secure.

Cut DragoTack Tape using a utility knife or scissors. Cut DragoTack Tape before removing the release liner for easier cutting. Install DragoTack Tape between 4°C and 43°C.

Review Drago Wrap's complete installation instructions prior to installation.

6. AVAILABILITY & COST

DragoTack Tape is available through our network of building supply distributors. For current cost information, contact your local Drago distributor or Stego Industries' Sales Representative.

7. WARRANTY

Stego Industries, LLC believes to the best of its knowledge, that specifications and recommendations herein are accurate and reliable. However, since site conditions are not within its control, Stego Industries does not guarantee results from the use of the information provided and disclaims all liability from any loss or damage. Stego Technology, LLC does offer a limited warranty on Drago Wrap. Please see www.stegoindustries.com/legal.

8. MAINTENANCE

Store DragoTack Tape in a dry and temperate area.

9. TECHNICAL SERVICES

Technical advice, custom CAD drawings, and additional information can be obtained by contacting Stego Industries or by visiting the website.

Email: international@stegoindustries.com

Contact Number: +1 (877) 464-7834

Website: www.stegoindustries.com

10. FILING SYSTEMS

- www.stegoindustries.com
- Buildsite

+1 (877) 464-7834 | www.stegoindustries.com

DATA SHEETS ARE SUBJECT TO CHANGE. FOR MOST CURRENT VERSION, VISIT WWW.STEGOINDUSTRIES.COM

