



STEGO™ CRETE CLAW™ TAPE (75 mm wide)

A STEGO INDUSTRIES, LLC INNOVATION | VAPOUR RETARDERS 07 26 00, 03 30 00 | VERSION: 31 DEC 2018

1. PRODUCT NAME

STEGO CRETE CLAW TAPE (75 mm wide)

2. MANUFACTURER

Stego Industries, LLC
216 Avenida Fabricante, Suite 101
San Clemente, CA 92672 USA
Sales, Technical Assistance
Ph: +1 (877) 464-7834
international@stegoindustries.com
www.stegoindustries.com



3. PRODUCT DESCRIPTION

USES: Stego Crete Claw Tape is a multi-layered tape that is used to seal Stego™ Wrap Vapour Barrier to the perimeter of the slab while the concrete is placed. Stego Crete Claw Tape allows wet concrete to cast into the textured top surface to form a mechanical bond/seal.

COMPOSITION: Stego Crete Claw Tape is composed of polyethylene film, aperture film, and an acrylic, pressure-sensitive adhesive.

SIZE: Stego Crete Claw Tape is 75 mm (3") x 55 m (180'). Stego Crete Claw Tape (75 mm Wide) ships 16 rolls in a case.

4. TECHNICAL DATA

TABLE 4.1: PHYSICAL PROPERTIES OF STEGO CRETE CLAW TAPE (75 mm wide)

PROPERTY	RESULTS
Dimensions	75 mm x 55 m (3" x 180')
Total Thickness	0.66 mm (26 mil)
Permeance: ASTM F1249	1.7 ng/(m ² *s*Pa) (0.03 gr/(ft ² *hr*in-Hg))
180° Adhesion Peel Strength: ASTM D903	3.1 kN/m (17.6 lbf/in)
Shear Adhesion Strength: 6.5 cm ² (1 in ²) shear test using an Instron 3345 Machine	>338 kPa (>49 lbf/in ²)*

* Specimens failed by stretching vapour barrier to failure before pulling Crete Claw from concrete.

5. INSTALLATION

SECURING STEGO WRAP TO SLAB: Clean surface of Stego Wrap to ensure that it is free of moisture, frost, dirt, and debris prior to the installation of Stego Crete Claw Tape. When ready to apply Stego Crete Claw Tape, peel back the release liner and apply to Stego Wrap. Stego Crete Claw Tape should be completely on Stego Wrap.

To detail, cut Stego Crete Claw Tape with a box knife or scissors. Stego Crete Claw Tape should be installed above 4°C for maximum adhesion. For additional information please refer to Stego's complete installation instructions.

TIP: Wrap the release liner back over the entire roll while unrolling Stego Crete Claw Tape. This technique will allow the release liner to pull off easily and keep it out of the way.

Continued...

Note – legal notice on page 2.

STEGO™ CRETE CLAW™ TAPE (75 mm wide)

A STEGO INDUSTRIES, LLC INNOVATION | VAPOUR RETARDERS 07 26 00, 03 30 00 | VERSION: 31 DEC 2018

6. AVAILABILITY & COST

Stego Crete Claw Tape is available through our network of building supply distributors. For current cost information, contact your local Stego Wrap distributor or Stego Industries' Sales Representative.

7. WARRANTY

Stego Industries, LLC believes to the best of its knowledge, that specifications and recommendations herein are accurate and reliable. However, since site conditions are not within its control, Stego Industries does not guarantee results from the use of the information provided herein. Stego Industries, LLC does offer a limited warranty on Stego Wrap. Please see www.stegoindustries.com/legal.

8. MAINTENANCE

Store Stego Crete Claw Tape in a dry and temperate area.

9. TECHNICAL SERVICES

Technical advice, custom CAD drawings, and additional information can be obtained by contacting Stego Industries or by visiting the website.

Email: international@stegoindustries.com

Contact Number: +1 (877) 464-7834

Website: www.stegoindustries.com

10. FILING SYSTEMS

- www.stegoindustries.com

+1 (877) 464-7834 | www.stegoindustries.com

DATA SHEETS ARE SUBJECT TO CHANGE. FOR MOST CURRENT VERSION, VISIT WWW.STEGOINDUSTRIES.COM

