PANGO CLAW® (3" WIDE)

A STEGO INDUSTRIES, LLC INNOVATION | VAPOR BARRIER 31 31 16, 07 26 00, 03 30 00 | VERSION: MAY 2, 2025

1. PRODUCT NAME

PANGO CLAW (3" WIDE)

2. MANUFACTURER

Stego Industries, LLC
216 Avenida Fabricante, Suite 101
San Clemente, CA 92672
Sales, Technical Assistance
Ph: (877) 464-7834
contact@stegoindustries.com
stegoindustries.com

3. PRODUCT DESCRIPTION

USES: Pango Claw is a multi-layered tape that is used to seal Pango® Wrap along its terminating edges (interior and perimeter) to the slab while the concrete is placed. Pango Claw allows wet concrete to cast into the textured top surface to form a mechanical bond/seal.

COMPOSITION: Pango Claw is composed of polyethylene film, polyolefin scrim, and an acrylic, pressure-sensitive adhesive.

SIZE: 3" X 180'

FEATURES AND BENEFITS: Pango Claw (3" Wide) ships 16 rolls in a case | Independent, university efficacy testing establishing termite barrier efficacy | Low water vapor permeance | Exceptional adhesion to Pango Wrap | Outstanding bond seal to concrete | Made in the USA

4. TECHNICAL DATA

TABLE 1: PHYSICAL PROPERTIES OF PANGO CLAW (3" WIDE)

PROPERTY	TEST METHOD	RESULTS
Total Thickness		26 mil
Permeance	ASTM F1249 – Test Method for Water Vapor Transmission Rate Through Plastic Film and Sheeting Using a Modulated Infrared Sensor	0.074 perms
180° Adhesion Peel Strength	ASTM D903	10.0 lbf/in.
Dimensions		3" x 180'

Note: perm unit = grains/(ft²*hr*in-Hg)

5. INSTALLATION

UNDER SLAB & CRAWL SPACE: Clean surface of Pango Wrap to ensure that it is free of moisture, frost, dirt, and debris prior to the installation of Pango Claw. When ready to apply Pango Claw, peel back the release liner and apply to Pango Wrap. Pango Claw should be completely on Pango Wrap. To detail, cut Pango Claw with a box knife or scissors.

TIP: Wrap the release liner back over the entire roll while unrolling Pango Claw. This technique will allow the release liner to pull off easily and keep it out of the way.

Continued...
Note – legal notice on page 2.

PANGO CLAW® (3" WIDE)

A STEGO INDUSTRIES, LLC INNOVATION | VAPOR BARRIER 31 31 16, 07 26 00, 03 30 00 | VERSION: MAY 2, 2025

5. INSTALLATION *Continued...*

Pango Claw should be installed above 40°F. In temperatures below 40°F take extra care to remove moisture or frost from the area of adhesion. Do not exceed 7 days between Pango Claw installation and concrete placement or full protection from UV and weather exposure.

For additional information, please refer to Pango's complete installation instructions.

6. AVAILABILITY & COST

For cost and availability of Pango Claw, please contact your local Stego® Sales Representative.

7. WARRANTY

Stego believes to the best of its knowledge, that specifications and recommendations herein are accurate and reliable. However, since site conditions are not within its control, Stego does not guarantee results from the use of the information provided herein. Stego offers a limited warranty on Pango Claw. Please see **stegoindustries.com/legal**

8. MAINTENANCE AND STORAGE

Maintenance: None required.
Storage and Handling: Store Pango Claw in a dry and temperate indoor area. Avoid direct sunlight and UV exposure. Avoid storing tapes in areas containing aromatic hydrocarbons, halogenated compounds, chlorinated compounds, oxidative agents, solvents or other known polyethylene solubilizers, prodegradants, as they may impact the product performance and/or service life. Handle with care to avoid damage.

Please refer to the Safety Data Sheet (SDS) for detailed safety, storage, and handling procedures.

9. TECHNICAL SERVICES

Technical advice, custom CAD drawings, testing information, and additional information can be obtained by contacting Stego or by visiting the website.

Email: contact@stegoindustries.com
Contact Number: (877) 464-7834
Website: **stegoindustries.com**

10. FILING SYSTEMS: stegoindustries.com

DATA SHEETS ARE SUBJECT TO CHANGE. FOR MOST CURRENT VERSION, VISIT STEGOINDUSTRIES.COM

Stego Industries, LLC ("Stego") Intellectual Property, Installation, Warranty, and State Approval Information: stegoindustries.com/legal.
©2025 Stego Industries, LLC. All rights reserved